2500 ANSI LUMENS

MULTI-PURPOSE

EASY TO SET UP

B O X 🔃 ISG H T

CD-850m

Operating a projector just got EASIER. Introducing the BOXLIGHT CD-850m. This 2500 lumen, XGA, MULTI-PURPOSE POWERHOUSE includes a COLOR-CODED CABLE AND INPUT SYSTEM, a built-in handle and INTUITIVE MENU System that makes set up a breeze for even the most infrequent or inexperienced users. Full of great features, the CD-850m includes full remote mouse function with BUILT IN LASER POINTER, digital keystone adjustment and digital zoom for FUMBLE-FREE IMAGE ADJUSTMENT. And "easy to use" doesn't include a sacrifice in image quality - the 800:1 CONTRAST RATIO and Faroudja video chip assure CINEMA-CLASS VIDEO PROCESSING. Call BOXLIGHT today!


BOXIJGHT

19332 Powder Hill Place Poulsbo, Washington 98370 800.762.5757 360.779.7901 www.boxlight.com



BOXLIGHT

CD-850m





- 2500 ANSI for any room size or lighting.
- Portable 9.35 pounds.
- 800:1 contrast ratio creates super sharp image definition.
- Quiet 35dB noise rating.
- Multiple inputs to connect several computers and peripheral systems at the same time.
- Digital zoom imaging allows you to see the fine details up close.
- Remote control with built-in laser pointer gives you a professional edge.
- Monitor loop-through.
- Zoom lens with large zoom range.
- Faroudja video processing.
- Color coded cables make it easy to connect all your equipment..
- All BOXLIGHT projectors feature the latest in technology and design.
- Lifetime 24/7 technical support.
- The fastest response time in the industry from our state-of-the-art service center.



To contact BOXLIGHT:

Direct	800.762.5757
Rental	800.736.6954
Education	800.689.6676
Government	800.497.4009
International	360.779.7901
Toll Free FAX	888.353.4242
Internet	www.boxlight.com

Lam Disp Con	ghtness np play Type ntrast Ratio	2500 ANSI lumens 250 watt, UHP	Horiz. Scan Frequency Vertical Refresh Rate	50-117 kHz 50-85 Hz
Disp Con	play Type		Vertical Refresh Rate	£0 8€ ∏-4
Con		O' I I' DIDIN DNDINDOD		30-03 112
	ntrast Ratio	Single chip DLP™ - DMD™ DDR	Projection Lens	Manual zoom and focus, 1:1.4 zoom ratio, F/1.9-2.3
0-1-	iliast italio	800:1	Diagonal Image Size	29-264 in / 70-670 cm
Cold	ors	16.7 million	Throw Distance	5-32.8 ft / 1.5-10 m
Asp	ect Ratio	4:3, 16:9 compatible	Keystone	Digital adjustment of +/- 20 degrees
Inpu	uts	Computer: (1) 15-pin, (1) M1-DA. Video: (1) RCA composite, (1) S-video,	Adjustments	On-board and remote
		(1) Component (RCA-type). Audio: (1) RCA (L/R), (2) computer mini-jack	Power Supply	100V-240V; 50/60 Hz
Out	tputs	Computer: (1) 15-pin. Control Port: for RS-232 control, USB for mouse	Power Consumption	350 watts
		operation. Audio: (1) RCA (L/R)	Compatibility	SXGA, XGA, SVGA, VGA, Mac
Aud	dible Noise	35 dB	Warranty	Two-year parts and labor (120-day lamp warranty)
Aud	dio	(2) built-in 2 watt speakers with audio loop-through	Accessories Included	Remote control with built in laser pointer, soft carry case, color coded cable
Vide	eo	NTSC, NTSC 4.43, PAL, PAL(BGDHI), PAL-M, PAL-N, PAL-60, SECAM		straps. Cables: M1-DA analog computer, RCA audio/video, US power cord,
HDT	TV/EDTV	Compatibility: 1080i, 720p, 576p, 480p		3.5 mm computer audio
Wei	ight	9.35 lb / 4.24 kg	Optional Accessories	Ceiling mount plate, suspension pole, round flush mount kit, lamp, various
FCC	C Rating	Class A Certification		screens and carrying cases.