

Dukane ImagePro 8751



DUKANE IMAGEPRO 8751



Brief Introduction

Beta 2.5

The Dukane ImagePro 8751 LCD projector has 1200 Ansi lumens, a contrast of 300:1 and an XGA 1024 x 768 resolution. Due to the brightness of 1200 Ansi lumens, a picture width of 302 cm is possible. In room light, the picture should be max. 201 cm wide. It is no longer offered by the manufacturer Dukane.



3 x 0,7" LCD TFT Panel
XGA 4/3 Liquid Crystal Display

Display Type

Ansi-Lumen

Contrast

Black Level

Offset

Resolution

Video Modes

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

Ceiling Mounting

Power

Size WxHxD

Operating Noise

1200

300:1 full on/off

4,0000 min. Lumen

XGA 1024 x 768

786.432 Pixel

SXGA 1280 x 1024 compressed

NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM

Standard-Portabel | External training and company presentations, as well as product presentations.

Small screen width, rooms with very little ambient light below 100 lumens.

150W UHB Lamp

Articel Nr.: 456-234

2000 h.

-

Manual

Manual 1,2

F=2,0-2,3

-

1W Mono

1 Computer(D-sub15 pin),
1-Video Input (Composite (RCA) x 1,
S-Video (4-pin DIN)),
RS232C- Mini jack x 1 (RGB use)
- RCA jack x 2 (video use)

-

220W

-

36dB

-

-

-

Frequenz

H-sync: 15,0-69,0 kHz

V-sync: 50-85 Hz

Foot-Lamberts

36 fL / max. 302 cm screen width
123 cd/m²



- Freeze
 - Blank (Black screen button)
 - Eco Mode
 - Kensington Slot
 - Gamma correction
 - Remote control with mouse control
- Discontinued (EOL) // Last update of the data: 2023-08-04

Features

Status
Data

More Details



HCinema

<https://www.projector-database.com/pro/DukanelImagePro8751-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.