Boxlight 6000





Brief Introduction

Beta 2.5

The 6000 LCD has 500 Ansi lumens, a contrast of 250:1 and an XGA 1024 x 768 resolution. An image width of up to 195 cm is possible as the projector has 500 Ansi lumens. However, if room light is available, the picture should be max. 130 cm wide. It is no longer offered by the manufacturer Boxlight.

Display Type

3 x 1,3" LCD TFT Panel

XGA 4/3 Liquid Crystal Display

Ansi-Lumen Contrast Black Level

Resolution

Video Modes

Projector 2,00 250:1 full on/off 2.0000 min. Lumen

250:1 full on/off 0.656 min. Lumen

Offset

XGA 1024 x 768 786.432 Pixel

SXGA 1280 x 1024 compressed NTSC, NTSC 4.43, PAL, PAL, SECAM

Standard-Portabel | External training and company presentations, as well as product

Application presentations.

Very narrow picture width and rooms with very little light.

120W UHP Lamp Light Source

Articel Nr.: BOX6000-930

Light Life 2000 h.

Operating Costs

Focus

Powered

Powered Zoom

Objective

Throw Ratio

Audio 2 x 2W

S-Video in

Cinch Stereo in D-sub 15pin in

Ceiling Mounting Power

Connections

Weight

Features

Size WxHxD **Operating Noise**

5,80 kg / 12,79 lbs.

Keystone Illumination

Frequenz

Foot-Lamberts 15 fL / max. 195 cm screen width

51 cd/m² ■ Freeze

Remote control with mouse control

Osram bulb only NLMP644


Lamp ruby Ruby-LMP644

Optional Lamp original BOX6000-930

> LMP-K633 Compatible lamp

Order here: https://www.hcinema.de/lampen/shop-en.php?id=n643 - Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data



More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.