

Model	OutWrite2 1.4 / OutWrite2 .5
Throw Ratio	1.4:1 / 0.5:1
IR Band	940 nm
Resolution	2560 x 1920
Frame Rate	60 FPS
Input Port	Micro USB (B type) (USB1.1 / USB2.0)
Calibration	Manual calibration with LightPen or interactive wand
Calibration Topology	4-Point
Driver	Auto install
Power Consumption	USB wire (5v, 500mA) direct use
Image Size	up to 120" diagonal
Dimensions (W x H x D)	4.8" x 1.1" x 3.2" / 122 mm x 28.2 mm x 81 mm
Weight	0.3 lbs / 0.142 g
SYSTEM REQUIREMENTS	
CPU	Core duo or above
RAM Size	512MB or above
Minimum Free Disk Space	100MB
INTERACTIVE DRIVER SUPPORT	
Windows	Microsoft Windows XP / Vista/ Windows 7 (32/64 bit) or above
MAC	MAC OS X v10.5 or above
Linux	Linux OS Ubuntu 10.04, Debian 5.0, and Suse 11
PACKAGE	
Box Dimension	17" x 6.1" x 2.8" / 43 cm x 15.5 cm x 7.1 cm
Weight	1.4 lbs / 600 g
Standard Accessories	LightPen, interactive wand, 4.5M USB cable, installation guide, user manual (CD), ceiling mount kit



Turn any projector into an interactive projector with this simple external add-on

Any flat surface can be upgraded to an interactive surface

Plug and Play for convenient installation (auto driver install)

Simple 4-point calibration

Connect USB cable and install driver directly from device

Throw Distance (ft)



Diagonal Image Size (in)

Throw Distance (ft)



Diagonal Image Size (in)

Award Winning Technical Support 24/7/365

And, of course, all BOXLIGHT products come with free lifetime technical support. Speak with a hands-on, in-house, ISF Certified® technician ready to service your projector should the need arise.

Please note: These throw charts are for a standard format projector