ChiStar CX 720





Brief Introduction Beta 2.5

Display Type

Ansi-Lumen

Contrast Black Level

Offset

Resolution

Video Modes

Application

Light Source Light Life

Operating Costs

Focus

Objective

Zoom

Throw Ratio

Audio

Connections

Ceiling Mounting Power Size WxHxD

Operating Noise

Weight

Keystone Illumination 95%

H-sync: 15-97 kHz Frequenz V-sync: 50-85 Hz

Foot-Lamberts 62 fL / max. 389 cm screen width

212 cd/m²

Features

Status

The standard portable CX 720 DLP projector from ChiStar has 2000 Ansi lumens, a contrast of 2000:1 and an SVGA 800 x 600 resolution. Thanks to the brightness of 2000 Ansi lumens, a picture width of 389 cm is possible. In room light, the image should be max. 259 cm wide. The projector is no longer sold by the manufacturer.

ω667 Lux (bei 200 cm Screen)

ក្ខី 2000:1 full on/off ១ 0,334 min. Lumen

1 x DLP Chip

SVGA 4/3 Ti Digital Light Processing Chip

2000 2000:1 full on/off

1,0000 min. Lumen

SVGA 800 x 600 480.000 Pixel

XGA 1024 x 768 compressed

PAL, SECAM, NTSC

Standard-Portabel | External training and company presentations, as well as product

presentations.

Medium screen width or rooms with little light, max. 100 lumens.

2000 h.

Manual

Manual

DVI Cinch Video in

Cinch Stereo in S-Video in **RS232C**

280 x 97 x 205 mm (11"x3,8"x8,1") 5,57 L/dm3

36dB

1,90 kg / 4,19 lbs.

Vertical

- Discontinued (EOL) // Last update of the data: 2023-08-04

Lux:667 Lux Room light max.: 133 Lux Candela pro m²:212 cd/m² Foot-Lamberts:62 fL 4/3 screen width:200 cm Screen:1 Gain

Data

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.