Chuangrong CR80SPL





Brief Introduction

Ansi-Lumen

Contrast Black Level 192 Ansi lumens, a contrast of 450:1 and an SVGA 800 x 600 resolution. As Chuangrong specifies the brightness of the projector in lumens, we have calculated an approximate Ansi lumen value in this case. An image width of up to 121 cm is possible, as the projector has 192 Ansi lumens. However, if room light is available, the picture should be max. 81 cm wide. It is no longer offered by the manufacturer Chuangrong.

Display Type

SVGA 4/3 Liquid Crystal Display

및 192 3200 Lumen

 Θ
 192 3200 Lumen

 φ64 Lux (bei 200 cm Screen)

 Θ
 450:1 full on/off

 φ64 Lux (bei 200 cm Screen)

 Θ
 0,4267 min. Lumen

 φ04 Lux (bei 200 cm Screen)

 Θ
 0,143 min. Lumen

Offset

Resolution SVGA 800 x 600 480.000 Pixel

Video Modes PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Application presentations.

Very narrow picture width and rooms with very little light.

Light Source 250W UHM Lamp

Light Life 1500 h. 2000 h. in Eco Mode

Operating Costs -

Focus Manual

Zoom Manual

Objective -

Throw Ratio -

Audio -

D-sub 15 pin in S-Video in Cinch Video in

Ceiling Mounting

Power

Connections

Size WxHxD

266 x 348 x 122 mm (10,5"x13,7"x4,8") 11,29 L/dm³

Operating Noise

Lux:64 Lux
Room light max.:13 Lux
Candela pro m²:21 cd/m²
Foot-Lamberts:6 fL

4/3 screen width:200 cm
Screen:1 Gain

Weight

Keystone Illumination

-

Frequenz

<u>Z</u>

Foot-Lamberts

6 fL / max. 121 cm screen width

21 cd/m²

Features

■ Eco Mode

Status

- Discontinued (EOL) // Last update of the data: 2024-06-04

Data









Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.