Compaq MP 1400











Brief Introduction Beta 2.5

800 x 600 resolution and a contrast of 400:1. The projector will be able to illuminate a picture width of 230 cm well. However, if room light is available, the picture width should ideally not exceed 153 cm. This model is no longer offered by Compag. 1 Chip DLP

With the MP 1400, manufacturer Compaq offers a standard portable DLP projector with SVGA

Display Type

SVGA 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast Black Level

700 400:1 full on/off 1,7500 min. Lumen

o 400:1 full on/off

Resolution

Offset

SVGA 800 x 600 480,000 Pixel

XGA 1024 x 768 compressed

Video Modes NTSC, PAL, SECAM, NTSC 4.43 PAL-M or PAL-N

Standard-Portabel | External training and company presentations, as well as product

presentations. Application

Small screen width, rooms with very little ambient light below 100 lumens.

- Lamp **Light Source**

Articel Nr.: L1551a

1000 h. Light Life

Operating Costs 83,33% / 0,35 €

Manual **Focus**

Zoom No Zoom

F=2,24 Objective

Throw Ratio

Audio

D-sub 15pin in

S-Video in Cinch Video in

Ceiling Mounting

Connections

185W

Power Size WxHxD

62 x 209 x 228,4 mm (2,4"x8,2"x9") 2,95 L/dm3

Operating Noise 40dB


Weight 1,90 kg / 4,19 lbs.

Keystone Illumination

Frequenz

21 fL / max. 230 cm screen width Foot-Lamberts

72 cd/m²



■ Gamma correction
■ Warping
■ Picture-in-Picture

■ Remote control with laser pointer

Osram bulb only NLMP992

Lamp ruby Ruby-LMP992

Optional Lamp original L1551A

Compatible lamp LMP-K15607

Order here: https://www.hcinema.de/lampen/shop-en.php?id=n992

- Discontinued (EOL) // Last update of the data: 2023-08-04

More Details

Status

Data





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.