

Everest BS W260



EVEREST BS W260



Brief Introduction

Beta 2.5

A brief introduction to the Everest BS W260. The LCD projector has a WXGA 1280 x 800 resolution and a contrast of 2000:1. As it is a short-throw projector, the projector can be positioned very close to the wall. For a 2 m wide image, the projector only needs to be 123 cm away from the screen. It is also Full HD 1080P compatible. This model is no longer offered by Everest.

Display Type



3 x LCD TFT Panel
WXGA 16/10 Liquid Crystal Display

Ansi-Lumen

3000

1200 Lux (bei 200 cm Screen)

Contrast

2000:1 full on/off

2000:1 full on/off

Black Level

1,5000 min. Lumen

0,601 min. Lumen

Offset

Resolution

WXGA 1280 x 800

1.024.000 Pixel

UXGA 1600 x 1200 compressed

Video Modes

Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p EDTV 480p, 576p

Disc Recognition

DVD | HD Blu-ray (komprimiert) | 3D Blu-ray | 4K UHD Blu-ray

Application

Short Distance | Medium screen width or rooms with a little more ambient light, max. 200 lumens.

Light Source

245W UHP Lamp

Light Life

-

Operating Costs

-

Focus

Manual

Zoom

No Zoom

Objective

F=1,8 f=8,2mm

Throw Ratio

0,615:1

Audio

10W Mono

Connections

HDMI 1.3 in
D-sub 15pin in und out
Cinch Video in
Cinch Stereo in
S-Video in
Mini Jack Audio in und out
USB Typ B in
RS232C Din 9 pin in
RJ45 in

Ceiling Mounting

Yes

Power

310W

Size WxHxD

348 x 132 x 360 mm (13,7"x5,2"x14,2") 16,54 L/dm³

Operating Noise

38,5 / 33 dB in Eco Mode

Weight

4,10 kg / 9,04 lbs.

Keystone

-

Illumination

-

Frequenz

H-sync: 31-92 kHz

V-sync: 48-120 Hz

Foot-Lamberts

111 fL / max. 556 cm screen width



380 cd/m²

- Full HD 1080P compatible
- Eco Mode
- Kensington Slot
- Lan network compatible.
- Short-throw projector

2013 Discontinued (EOL) // Last update of the data: 2023-08-04



HCinema

<https://www.projector-database.com/pro/everestbsw260-en.html>

More Details

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.