

Projector XP80

Compact projector for business presentation

Issue July 2007

Pages 2

With outstanding performance and compact dimensions the Projector XP80 from Fujitsu Siemens Computers will brighten up any presentation.

The Projector XP80 offers high resolution and contrast, excellent brightness and very low weight. This makes the Projector XP80 the ideal choice for busy travelling users or business executives, even for presentations in fully lit rooms.

Reliability

- High quality and stability
- Reliability of delivery
- Single Chip DLP™ XGA-technology

Ergonomics

- Digital Keystone correction
- High contrast and excellent focus
- 1700 lumens for best visual experience

Usability

- Very low weight 1.1 kg
- Integrated loudspeaker
- Easily user replaceable lamp
- Ease-of-use multi-language OSD menu
- Plug & Play
- Digital and analogue PC, Composite, S-Video and Audio connectivity
- HDTV compliant



Technology	Single Chip DLP™ XGA
Contrast typical	2000 :1
Brightness typ	1700 lm
Colors	16.7 Million/24bit
Optics	
Lens	1.16:1 manual
Diagonal image size	0.8 – 5.3 m
Throw distance	1.5 – 10 m
Keystone correction	+/- 5 degrees digital
Uniformity	70%
Frequencies	
Horizontal	15 - 90 kHz
Vertical	50 - 85 Hz
Bandwidth	112 MHz
Supported Graphic Modes/Formats	
Pixels	1280 x 1024
Pixels	1152 x 864
Pixels	1024 x 768 (native)
Pixels	1400 x 1050
Pixels	1280 x 800
Pixels	140 x 900
Pixels	832 x 624 (MAC)
Pixels	800 x 600
Pixels	640 x 480
Video Input Compatibility/Modes	
NTSC, PAL, Secam, SDTV (480i), EDTV (480p), HDTV (720p, 1080i)	
Input Sources	
Computer	DVI-I (with HDCP support)
Video	S-Video, Composite
Audio	2.6 mm mini jack
Control	USB for service only
OSD languages	English, French, Spanish, German, Italian, Japanese, Korean, Swedish, Chinese, Russian, Portuguese

Electrical values	
Rated voltage	100-240 V, +/- 10%
Frequency	50-60 Hz
Power draw	
Operating (normal/eco)	< 195 W/ 165 W
Standby mode	< 8 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	5°C to 35°C
Dimensions (H x W x D)	73.5x192.3x164.5 mm
Weight	1.1 kg
Operating noise typical	38 db(A)
Reliability typical	
Lifetime of Lamp normal(eco)	5000h (4000h)
Compliance with standards	
Product safety	UL 1950 CSA 22.2 No.950 FCC Class A
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024, EN61000-3-2/-3);
Supplied material	
Cables / adapter	DVI-I to VGA Cable with USB, 1,8 m 3 pole Power Cable, 1.8 m Audio cable (mini jack), 1,8 m Composite Video Cable, 1,8 m
Accessories	Soft carrying case Remote control Lens cap User guide on CD
Warranty	Projector XP80: 2 years Lamp: 90 days or max. 500 hours
Special features	Kensington Lock prepared User replaceable lamp
Order Code	S26361-K1215-L100
EAN Code	4 333 64 30 90 678