


GROVIEW B2D

GROVIEW B2D



Display Type	 1 x LCD Panel HDTV 16/9 Liquid Crystal Display	
Ansi-Lumen	-	Lux (bei 200 cm Screen)
Contrast	1000:1	-
Black Level	-	-
Offset	-	-
Resolution	HDTV 1280 x 720 921.600 Pixel HDTV 1920 x 1080 compressed	
Video Modes	Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, EDTV 480p, 576p	
Application	Game-Portabel Very portable, small-screen projections. Very narrow picture width and rooms with very little light.	
Light Source	LED	
Light Life	30000 h.	
Operating Costs	0,00 € LED	
Focus	Powered	
Zoom	No Zoom 75%-100% Digital	
Objective	-	
Throw Ratio	-	
Audio	-	
Connections	HDMI in Mini Jack Audio out USB in Bluetooth 5.1	
Ceiling Mounting	Yes	
Power	-	
Size WxHxD	121,9 x 175,3 x 144,8 mm (4,8"x6,9"x5,7")	3,05 L/dm ³
Operating Noise	20dB	
Weight	1,36 kg / 2,2 lbs.	
Keystone	-	
Illumination	-	
Frequenz	-	

Foot-Lamberts -

-

Features ■ Full HD 1080P compatible
■ Wi-Fi network compatible.

-

Optionaler Zubehör

Status 2024 Current model // Last update of the data: 2024-11-05



HCinema

<https://www.projector-database.com/pro/groviewb2d-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.