


InFocus LP290

INFOCUS LP290



Brief Introduction

Beta 2.5

Display Type



3 x 0,7" LCD TFT Panel
XGA 4/3 Liquid Crystal Display

Ansi-Lumen

1100

356 Lux (bei 203 cm Screen)

Contrast

400:1 full on/off

400:1 full on/off

Black Level

2,7500 min. Lumen

0.897 min. Lumen

Offset

-

Resolution

XGA 1024 x 768

786.432 Pixel

Video Modes

SXGA 1280 x 1024 compressed

NTSC, PAL, SECAM, PAL-M und PAL-N

Application

Standard-Portabel | External training and company presentations, as well as product presentations.

Light Source

Small screen width, rooms with very little ambient light below 100 lumens.

Light Life

132W UHP Lamp

Articel Nr.: SP-LAMP-LP2E

2000 h.

Operating Costs

-

Focus

Manual

Zoom

Manual 1,3

Objective

-

Throw Ratio

-

Audio

2 x 1W Mono

Connections

D-sub 15pin in und out

S-Video in

Cinch Video in

USB

Ceiling Mounting

Yes

Power

200W standby 5W

Size WxHxD

211 x 76 x 269 mm (8,3"x3"x10,6") 4,31 L/dm³

Operating Noise

34dB



Weight	2,60 kg / 5,73 lbs.
Keystone	-
Illumination	75%
Frequenz	H-sync: 15-100 kHz V-sync: 43,5-130 Hz
Foot-Lamberts	33 fL / max. 289 cm screen width 113 cd/m²
Features	■ Freeze ■ Kensington Slot ■ Remote control with laser pointer und mouse control Bulb only Philips Lamp ruby Lamp original Compatible lamp Universal Remote original NLMP389 Ruby-LMP389 420059 / SP-LAMP-LP2E LMP-K15652 Fernb-uni-V3
Optional	
Status	Order here: https://www.hcinema.de/lampen/shop-en.php?id=n1878 2001 Discontinued (EOL) // Last update of the data: 2023-08-04

Data



More Details



HCinema

<https://www.projector-database.com/pro/infocuslp290-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.