

iRULU P6

iRULU P6



Display Type	 1 x LCD TFT Panel WXGA 15/9 Liquid Crystal Display	
Ansi-Lumen	-	Lux (bei 200 cm Screen)
Contrast	3000:1	-
Black Level	-	-
Offset	-	-
Resolution	WXGA 1280 x 768 983.040 Pixel	
Video Modes	Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, EDTV 480p, 576p	
Application	Standard-Portabel External training and company presentations, as well as product presentations. Very narrow picture width and rooms with very little light.	
Light Source	145W LED	
Light Life	50000 h.	
Operating Costs	0,00 € LED	
Focus	Manual	
Zoom	No Zoom	
Objective	F=1,70	
Throw Ratio	-	
Audio	3W	
Connections	HDMI in DVI in D-sub 15pin in und out Cinch Video in Cinch Stereo in S-Video in Mini Jack Audio in und out USB in RS232C Din 9 pin in RJ45 in	
Ceiling Mounting	Yes	
Power	-	
Size WxHxD	320 x 120 x 260 mm (12,6"x4,7"x10,2") 9,98 L/dm³	
Operating Noise	-	
Weight	2,60 kg / 5,73 lbs.	

Keystone Illumination	Vert.: +/-15° -
Frequenz	-
Foot-Lamberts	- -
Features	■ Full HD 1080P compatible ■ Wi-Fi network compatible. ■ Lan network compatible. ■ Chipset: Amlogic S905X Quad-Core Cortex-A53@1.5GHz(DVGFS) ■ GPU: Penta-Core Mali-450 up to 750MHz(DVFS) ■ FLASH: 8GBNAND FLASH ■ SDRAM: 1GBDDR3
Status	2017 Discontinued (EOL) // Last update of the data: 2023-08-04 Created: 2018-03-18 15:38:42



More Details



HCinema

<https://www.projector-database.com/pro/irulup6-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.