



Kindermann KX 3460W

Powerful and compact

Light output 3200 lumens (ANSI)

Resolution WXGA (1280 x 800)

Low noise level 30 dBA / ECO

- Presentation from internal memory (1.5 GB) or USB without PC
photo, video, audio, PDF, Word, Excel, PowerPoint
- Image transmission via LAN or WLAN with optional WLAN drive
- LAN control compatible with AMX D.D., Crestron RoomView™, PJ Link
- Numerous automatic functions
- Free APP for projection
e. g. from iPad (iOS, Android)



TECHNICAL DATA		Kindermann KX 3460W
Ref. No.		3000 000 759
Native resolution (pixels)		WXGA (1280 x 800)
Supported resolutions		VGA - UXGA / 1080p
Lumens		3200
Display type		LCD
Contrast ratio		1000 : 1
Frequency: horizontal, vertical		32 - 92 kHz, 48 - 120 Hz
Focal length in mm		18.5 - 22.2
Image diagonal in m		1 - 7.62
Projection distance in m		1.1 - 10.6
Ratio (distance : image width)		1.54 - 1.85 : 1
U/D-Ratio/Offset		7:1 / -
Interchangeable lenses		no
Lamp		245 UHP
Noise level		30 dB eco
Dimension in mm (BxHxT)		325 x 110 x 265
Weight in kg		3.4
INPUTS / OUTPUTS		
Computer VGA (analogue)		2 x HD15
DVI/HDMI (digital)		1 x HDMI
Video		1 x Cinch
S-Video		1 x 4-pin MiniDIN
Component Video		via VGA
RS232 interface		1 x RS232 (9-pin)
LAN control		1 x LAN/RJ45
Mouse interface		-
USB		yes
Audio (computer)		2 x 3.5 mm stereo jack
Audio (video)		1 x Cinch x 2
Monitor output		yes (variable in/out)
Audio output		yes
FEATURES		
Keystone correction (digital)		vertical ± 30°
Loudspeaker		1 x 10 W
Presentation via LAN/WLAN		yes/optional
Presentation from memory medium		yes, 1 x USB/A, 1 x MiniUSB
Safety features		Kensington lock, security bar, password protection
Laser pointer in IR remote control		yes
Voltage		100 - 240V AC, 50 - 60 Hz
Special features		-
Lamp warranty		3 years or 1000 hours (whatever comes first)
Warranty (bring-in)		3 years in Europe, 2 years outside Europe
Package includes		Standard lens, IR remote control with laser pointer, power supply, VGA cable, quick guide, operating instructions (CD), softbag