



Kindermann KX 7000WU

WUXGA installation projector with high flexibility

Light output 5500 lumens (ANSI)

Resolution WUXGA (1920 x 1200)

Low fan noise 32 dBA / ECO

- 3LCD technology
- Standard lens with motor zoom (R=1.3-2.1:1 / 1.6 fold), motor focus and motor shift
- Numerous interchangeable lenses: wide angle with R=0.8:1 (fix) and tele with R=2.8-4.6:1



TECHNICAL DATA	Kindermann KX 7000WU
Ref. No.	3000 000 945
Native resolution (pixels)	WUXGA (1920 x 1200)
Supported resolutions	VGA - UXGA, Mac
Video	480i - 1080p, PAL/SECAM/NTSC/NTSC4.43/PAL-M/PAL-N
Lumens	5500 / 4500 (eco)
Display type	3 x 0.76" LCD
Contrast ratio	500 : 1
Image uniformity	80 %
Frequency: horizontal, vertical	15 - 100 kHz, 48 - 120 Hz
Focal length in mm	standard: f= 21.3 - 34.16 mm, F=1.7 - 2.2, motor zoom = 1.6x
Lens shift	H: +/- 50% max., V: +/- 10% max., motorized
Image diagonal in cm	30" - 300" / 77 - 768 cm
Image format	16:10 (native), 16:9, 4:3 compatible
Projection distance in m	0.8 - 13.6 m
Ratio	standard lens 1.3 - 2.1 : 1
Interchangeable lenses	R= 0.8 : 1 fix, R= 1.3 - 1.7:1, R= 2.8 - 4.6:1
Lamp	330 W USHIO; lamp life typ. 2000 h / 3000 h (eco)
Lamp warranty	1000 h or 3 years, (whatever is reached first)
Noise level	38 dB, ECO mode: 32 dB
Dimension in mm	535 x 190 x 390 mm (BxHxT)
Weight in kg	10.8 kg (with standard lens)
Voltage	100 - 240 V AC, 50/60 Hz
Power input standard	standard: 420 W, eco mode: 340 W
Power input standby	0.4 W
Operating temperature	5° - 35°C
Humidity	20% - 85%
INPUTS / OUTPUTS	
Computer VGA (analogue)	1 x HD15, 1 x HD15 switchable IN / monitor OUT, 1 x BNC x 5 (RGBHV)
DVI / HDMI / DP/ (digital)	1 x DVI-D (with HDCP), 1 x HDMI
Video	1 x cinch
S-video	1 x mini DIN 4 pin
Component video	1 x BNC x 3 (RGBHV)
Control	1 x RS232 (DB 9 plug); LAN (RJ45)
Audio (computer)	1 x 3.5 mm stereo jack
Audio (video)	1 x cinch x 2
Monitor output	1 x HD15 switchable IN / monitor OUT
Audio output	1 x 3.5 mm stereo jack
SPECIAL FEATURES	
Keystone correction (digital)	vertical: +/- 40° (manual)
Integrated loudspeaker	1 x 7 W
Others	lamp change and filter cleaning possible when mounted on the ceiling; Anti-theft device (password, safety rod); Quick Power OFF; direct start when power is on
Package includes	IR remote control, power supply, VGA cable, operating instructions (CD)
Warranty (bring-in)	3 years in Europe, 2 years outside Europe