Nec NC3240S-A





width is smaller (we recommend max. 1055 cm), rooms with residual light are also no problem.

The model is also Full HD 1080P and 4K compatible. On the market since 2011, the model is no longer offered by the manufacturer Nec, but is still very popular in our projector database.

2000:1 full on/off 7,83 min. Lumen

დ15644 Lux (bei 200 cm Screen)

Brief Introduction Beta 2.5

Display Type

Contrast

Offset

Black Level

Application

Light Source

3 x 1,38" DLP Chip UHD 19/10 Ti Digital Light Processing Chip

Ansi-Lumen 33000 / mit 7.0KW Lampe

2000:1 full on/off 16,5000 min. Lumen

UHD (4K+2K) 4096 x 2160 Resolution

8.847.360 Pixel

Video Modes Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 4K UHD, EDTV 480p, 576p

E-Cinema | Digital Cinema (D-Cinema) in the movie theater.

Very large screen width and rooms with plenty of light and shaded daylight.

NC-32PS01 (7kW LPSU) / NC-32PS02

(4kW LPSU) Lamp

Articel Nr.: 60002998 / NC-80AF01

Light Life h.

Operating Costs

Focus Powered

Zoom Powered

optional Objective

Throw Ratio optional

Audio No

> D-sub 15 pin in HD-SDI in 2 x DVI in

Connections RS232C Din 9 pin in

> USB Typ A RJ45 Nein

Ceiling Mounting

Power

Size WxHxD 594 x 398 x 452 mm (23,4"x15,7"x17,8") 106,86 L/dm3

Operating Noise 66dB

Lux:15644 Lux Room light max.:3129 Lux Candela pro m²:4978 cd/m² Foot-Lamberts:1453 fL 19/10 screen width: 200 cm Screen:1 Gain

Weight 97,00 kg / 213,85 lbs.

Keystone Illumination

Frequenz

Features

Foot-Lamberts 1453 fL / max. 1582 cm screen width

4978 cd/m²

■ Full HD 1080P compatible

■ Control via web browser Lan network compatible.

■ Integrated Media Block (IMB) and Local Storage Server

4 x projector air filter original 60002999 / NC-80AF02

Optional 60002998 / NC-80AF01 6 x lamp air filter original

Order here: https://www.hcinema.de/lampen/shop-en.php?id=fi9000972

Optional Lenses

Name	Ratio	Distance	Shift V	Shift H	Zoom
Zoom Optional Lenses					
NC-50LS21Z	2.71-3.89:1	5.4-7.8 m			Powered
NC-50LS18Z	1.95-3.26:1	3.9-6.5 m			Powered
NC-50LS16Z	1.63-2.7:1	3.3-5.4 m			Powered
NC-50LS14Z	1.44-2.16:1	2.9-4.3 m			Powered
L2K-30ZM	3-4.3:1	6-8.6 m			Powered
L2K-12ZM	1.13-1.31:1	2.3-2.6 m			Powered
2K-14ZM	1.3-1.85:1	2.6-3.7 m			Powered
Status	2011 Discontinued (EOL) // Last update of the data: 2023-08-04				

Data







More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.