## Norxe P55 6K n-shift





Brief Introduction

The Norxe P55 6K n-shift stationary laser DLP projector has 2500 Ansi-Lumen, a contrast of 2000:1 and a 6K 6144 x 3456 resolution. It is a laser projector with a 100,000-hour light lifespan, which would be the equivalent of over 68.5 years at 4 hours a day. An image width of up to 435 cm is possible. However, the image should be smaller if room lighting is used. We recommend a maximum of 290 cm. If the image width is insufficient, the projector offers integrated edge blending software, which allows several projectors to project a large image together. Furthermore, it is Full HD 1080P compatible, and can thus project Blu-rays even onto the ceiling using 360° projection.

1 x DMD DLP Chip

თ833 Lux (bei 200 cm Screen)

ଦ୍ଧି 2000:1 0,417 min. Lumen

Display Type

K 4/3 Ti Digital Light Processing Chip

Ansi-Lumen Contrast 2500 2000:1

Black Level

ថ្មី 1,2500 min. Lumen

Offset

Resolution

Application

Light Source Light Life 6K 6144 x 3456

21.233.664 Pixel mit E-Shift

Video Modes Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, EDTV 480p, 576p

Stationary | Permanent installation in the training room and meeting room as well as the

conference room.

Medium screen width or rooms with little light, max. 100 lumens.

Laser SSI, NXL® + optional IR LED

100000 h. bis 50% Helligkeit

Operating Costs

0,00 € LED

Focus Powered

Zoom Powered

Objective optional

Throw Ratio optional

Audio -

2x DisplayPort 1.4

HDMI 2.0 in

Connections 2x BNC (Sync/Trigger)
Mini Jack Audio in und out

Mini USB Mini DIN Yes

Ceiling Mounting Ye

Power 440W Max / 400W Normal

Size WxHxD 485 x 216,75 x 405 mm (19,1"x8,5"x15,9") 42,43 L/dm<sup>3</sup>

Lux:833 Lux
Room light max.:167 Lux
Candela pro m²:264 cd/m²
Foot-Lamberts:77 fL

4/3 screen width:200 cm
Screen:1 Gain

Operating Noise

Weight 18,50 kg / 39,68 lbs.

Keystone -Illumination -

Frequenz -

Foot-Lamberts 77 fL / max. 435 cm screen width

264 cd/m<sup>2</sup>

■ Full HD 1080P compatible

Warping

■ 360° installable

■ 24/7 continuous operation capable

Features ■ Edge Blending

■ Password protection

■ Lan network compatible.

■ Unify<sup>™</sup> Web, Unify<sup>™</sup> Desktop

■ Native 4K@60–240Hz

## Optionaler Zubehör

## **Optional Lenses**

Name	Ratio	Distance	Shift V	Shift H	Zoom
		Zoom Optional I	_enses		
N4	1.35-2.27:1	2.7-4.5 m	+/-110%	+/-72%	Powered
N2	1.05-1.4:1	2.1-2.8 m	+/-116%	+/-75%	Powered
N1	0.7-1.09:1	1.4-2.2 m	+/-53%	+/-51%	Powered
		Fix Optional Le	enses		
N3	0.55:1	1.1 m	+/-87%	+/-63%	No Zoom
Status	2024 Current model // Last update of the data: 2025-02-10 Created: 2024-11-13 15:51:45				

Data



More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.