

RICOH PJ TS100

RICOH
imagine. change.

Projector



PJ TS100

MAIN SPECIFICATIONS

GENERAL

Projection system:	Single chip DLP
Resolution:	480,000 pixels (800 x 600)
Panel:	0.55 inch
Brightness:	PJ TS100: 3,000 lumen
Colour reproducibility:	1,073,000,000 colours
Native contrast ratio:	2,200:1
High contrast ratio:	10,000:1
Projection screen size:	30" to 300"
Projection distance:	120 to 1,200 cm (from rear of unit to projection surface)
Throw ratio:	1.95-2.15
Lamp:	High-pressure mercury lamp
Lamp life:	Standard: 4,500 hours (190 W) Eco mode 1: 6,000 hours (190 W)
RGB compatible signals	Real display: SVGA, VGA Compressed representation:
(analogue, digital):	UXGA, SXGA, WXGA, XGA
Input signals:	NTSC, PAL, SECAM, NTSC4.43, PAL-M, PAL-60
Analogue RGB compatible scanning frequency:	Horizontal: 30 to 100 kHz Vertical: 50 to 85 Hz
Zoom ratio:	1.1 (manual)
Connection terminal (PJ TS100):	Mini D-SUB15pin x 1 (Computer 1 IN), SUB 9pin x 1 (RS-232C), USB-TYPE-minIB x1
Primary features:	Mute (Blank), Freeze, Re-size (Magnify), Eco mode, 3D projection (Ready), Wall Color mode, Security bar, Kensington lock
Dimensions (W x D x H):	314.2 x 223.5 x 101.7 mm
Weight:	2.6 kg
Supported languages:	English, German, French, Italian, Spanish, Dutch, Swedish, Norwegian, Danish, Finnish, Hungarian, Czech, Polish, Portuguese, Russian, Korean, Traditional Chinese, Simplified Chinese, Turkish, Arabic, Indonesian, Japanese, Thai
Power source:	100 - 240 V, 50/60 Hz

ECOLOGY

Power consumption:	Operating power: 267 W Energy Saver mode: 224 W Stand-by mode: 0.5 W
Operating temperature:	5°C - 40°C
Operating humidity:	80%
Storage conditions:	Temperature: 20 - 60°C
Noise level:	Standard: 34 dB Eco: 31 dB

ACCESSORIES

RGB cable, Power cable, CD-ROM and manual, Remote control with batteries

CONSUMABLES

Replacement lamp Type14

For availability of models, options and software, please consult your local Ricoh representative.

ISO 9001: 2000 certified
ISO 14001 certified

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

The images in this brochure are not real photographs and slight differences in detail might appear.

RICOH
imagine. change.

URL: <http://www.ricoh.co.in>

RICOH INDIA LIMITED

CORPORATE OFFICE: 2nd Floor, Sakon Aurum Building, Plot No. 4, District Centre, Jasola, New Delhi-110 025
Tel: (011) 49103000, 49103100, 49103200 Fax: (011) 49103099, 49103199 Email: ril.info@ricoh.co.in SMS: 'RICOH' to 53456
REGISTERED OFFICE: 801, 8th Floor, Akruti Star, MIDC Central Road, Andheri-East, Mumbai - 400 093
Tel: (022) 66833000 Fax: (022) 67032099
Ahmedabad, Bangalore, Bhopal, Bhubaneswar, Chandigarh, Chennai, Coimbatore, Delhi, Gurgaon, Guwahati, Hyderabad, Jaipur, Kochi, Kolkata, Lucknow, Mumbai, Nagpur, Noida, Patna, Pune, Ranchi, Visakhapatnam.

For more information, please contact: