



PLC-XE50

- XGA Resolution (1024 x 768)
- 1500 ANSI Lumen
- 600:1 Contrast Ratio
- Digital Keystone Correction
- Ultra short throw lens (80" Diagonal Screen @ 9cm distance)
- Anti-Theft Alarm
- No external buttons

PLC-XE50

TECHNICAL DETAILS	PLC-XE50
Category	Education
Panel	0.8 inch TFT p-Si x 3
Lamp	Single 275W Lamp
Brightness ANSI lumens	1,500
Lamp Service Life	3,000 h (eco mode)/2,000 h (normal mode)
Fan Noise	25 dB (eco mode)/30 dB (normal mode)
Standard Lens	F = 1.65–1.83 / f = 22.5–27.0 mm*
Contrast Ratio	600 : 1
Resolution in pixels	2,359,296 (1024 x 768 dots)
Uniformity	80%
Bandwith/Frequency	H/V sync ~ 15-100kHz ~ 50-100Hz, Dot clock 140 MHz
Colour Systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Connections	Input 1: 1 x Dsub 15 Input 2: 1 x Dsub 15 (Switchable) Input 3: 3 x RCA (Component) - S-Video 1 x RCA (Composite) Audio Out: Computer: Minijack stereo. Communication Terminal: RS232C (Mini DIN 8 Pin)
Keystone Correction	vertical +/- 5°
Computer Compatibility	UXGA/ SXGA+ / SXGA/ WXGA/ SVGA/ VGA/ MAC
Power Consumption/Voltage	100V-240V AC (auto voltage)
Warranty	3 years
Dimensions (W x H x D)	374 x 196.8 x 495 mm
Weight	7.6kg

* You can use the distance calculator at www.sanyo.co.uk to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 09/2007

Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.sanyo.co.uk

