PLC-XP57L

High Brightness Projector

Main Features:

- **XGA Resolution (1024 x 768)**
- **High Brightness, 5,500 ANSI**
- **DVI-D/ VGA & RGBHV Connectivity**
- **1000:1 Contrast Ratio**
- **Vertical Lens Shift**
- **10 bit Processing for Improved Video Performance**
- **One Touch Interchangeable Lens System**
- **Optional Short & Long Throw Lenses**
- **Optional Network Connection (POA-PN03)**

Model name	PLC-XP57L
Panels	1.3 inch TFT p-Si x 3
No. of pixels	2,359,296 (1024 x 768 dots)
Projection lamp	Single 318W UHP Lamp
Brightness	5,500 ANSI lumens
Contrast	1000:1
Uniformity	90% (corner to centre)
Up-Down Ratio/ Keystone Correction	Lens shift 10:0~1:1(U/D), Digital keystone U/D/+/- 40° U/D/+/- 20°
Projection lens	Not supplied as standard
Optional lenses	LNS-W32/ W31A/ S30/ S31/ T31A/ T32
Terminal	Input1: DVI-D (DHCP)/ VGA (D-Sub15)/ Monitor Out Input2: RGBHV (BNCx5)/ Y,Pb/ Cb,Pr/Cr (BNC x3) Input3: Composite RCA/ S-Video/ Y,Pb/Cb, Pr/Cr (RCA)
Audio Out	Computer: Minijack stereo. Video: RCA (L/R)
Communication Terminal	RS232C (Mini DIN 8 Pin)
Computer compatibility	UXGA/ SXGA+ / SXGA/ WXGA/ SVGA/ VGA/ MAC
Video Compatibility	HDTV 1080 60i/ 50i- 24/25/30psf- /720p/ 575p/ 480p/ 575i/ 480i
Colour systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Scanning frequency	H/V sync ~ 15-100kHz ~ 48-100Hz, Dot clock 180 MHz
Voltage	100V-240V AC (auto voltage)
Dimensions (W x H x D)	319 x 168 x 430 mm
Weight	7.9 kg (Without Lens)

Specifications subject to change without notice