

PLC-XU110 | PLC-XU100

Brilliant Ideas for Your Business.

SANYO

- Resolution, native: XGA (1,024 x 768), maximum: UXGA (1,600 x 1,200)
- Brightness: 4,000 ANSI lumens
- Light weight of only 3.3 kg (PLC-XU100)
- Anti-theft function: audio alarm feature (PLC-XU110)
- Network integration with LAN connector (RJ45, PLC-XU110)
- WLAN USB key (PLC-XU110)
- DVI-D input (PLC-XU110)
- 3-year warranty, 1 year lamp warranty



PLC-XU110 | PLC-XU100

Brilliant Ideas for Your Business.



TECHNICAL DATA	PLC-XU110	PLC-XU100
Category	Business	
Panel	3 x 0.8" TFT p-Si (4 : 3), micro lens	
Projection Lamp	300 W UHP (LMP-103)	
Brightness in ANSI lumens	4,000 ANSI lumens	
Lamp Life	1,500 h (High Mode), 2,500 h (Eco Mode)	
Fan Noise	35 dB (High Mode), 30 dB (Eco Mode)	
Standard Lens	F = 1.7 – 2.1/f = 26.7 – 32 mm	
Aspect Ratio	1.62 – 1.97 : 1	
Throw Distance	1.3 – 10.0 m (You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances.)	
Contrast Ratio	500 : 1	
Resolution in Pixels	1,024 x 768 (XGA)	
Horizontal Resolution	600 TV lines	
Uniformity	85 %	
Bandwidth/Frequency	140 MHz, horizontal 15 ~ 100 kHz, vertical 50 ~ 100 Hz	
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N	
Connections	Input 1: DVI-I (digital/HDCP/analogue) Input 2: 1 x D-Sub15 (RGB/Component) Input 3: 1 x RCA (Composite), 1 x Mini DIN 4-pin (S-Video) Audio: 2 x RCA (R/L Mono) for video, 1 x 3.5 mm stereo jack for computer Monitor Output: 1 x D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input Jack 1: Mini DIN 8-pin (RS232) Control Input Jack 2: USB Type B 1 x USB (Type A) for WLAN Key, 1 x RJ45 (LAN)	Input 1: 1 x D-Sub15 Input 2: 1 x D-Sub15 (RGB/Component) Input 3: 1 x RCA (Composite), 1 x Mini DIN 4-pin (S-Video) Audio: 2 x RCA (R/L Mono) for video, 1 x 3.5 mm stereo jack for computer Monitor Output: 1 x D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control input jack: Mini DIN 8-pin (RS232)
Audio Function	1 W Mono	
Keystone Correction	Vertical +/-40	
Lens Shift/ U/D Ratio	9 : 1 (Fixed U/D Ratio)	
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)	
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA	
Zoom/Focus	1.2 x	
Power Consumption	390 W	385 W
Warranty	3 years, 1 year lamp	
Dimensions (W x H x D)	334 x 78 x 232 mm	
Weight	3.5 kg	3.3 kg
Standard Accessories	Operating manual, power cable, IR remote control with laser pointer + mouse function, batteries, USB cable (Type A and B), VGA cable, PIN code label, alarm function, carrying case, USB Wireless LAN adapter (POA-USB11G)	Operating manual, power cable, IR remote control, VGA cable, PIN code label
Optional Accessories	SCART-VGA cable (POA-CA-SCART), USB memory (POA-USB02)	SCART-VGA cable (POA-CA-SCART), Remote control with laser pointer (POA-RC KIT03) Presentation KIT including mouse function (POA-RC KIT04)
Lenses	Standard Lens	



Technical specifications subject to change without notice. Date 09/2006

