SVIC S720H





Display Type

Resolution Video Modes 1 x 7" LCD TFT Panel 4/3 Liquid Crystal Display

Ansi-Lumen 132 2200 Lumen 800:1 full on/off Contrast Black Level Offset

0,1650 min. Lumen

NTSC, PAL, SECAM, NTSC 4.43, EDTV, HDTV 1080i, 1080p, 720p, 1080p

Standard-Portabel | External training and company presentations, as well as product presentations.

ω44 Lux (bei 200 cm Screen)
800:1 full on/off
0,055 min. Lumen

Application Very narrow picture width and rooms with very little light.

Light Source Light Life

6000 h. **Operating Costs**

Focus

Zoom

Objective

Throw Ratio


Audio 2 x 2W


> **HDMI 1,2** D-sub 15 pin in Scart in YUV in S-Video in Cinch Video in

Cinch Stereo in und out

Antenne in SD Card Slot

Connections





Ceiling Mounting -

Power -Size WxHxD -Operating Noise 28dB

Weight

-

Keystone

Vertical

Illumination

_

Frequenz

-

Foot-Lamberts

4 fL / max. 100 cm screen width

14 cd/m²

■ Full HD 1080P compatible

■ Password protection

Features

■ Faroudja DCDi

■ Digital Zoom ■ De-Interlace

Status Data - Discontinued (EOL) // Last update of the data: 2024-05-29

More Details



Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.