Vivitek D418V/S







Brief Introduction

Beta 2.5

The standard portable D418V/S DLP has 2100 Ansi lumens, a contrast of 2000:1 and an SVGA 800 x 600 resolution. An image width of up to 399 cm is possible as the projector has 2100 Ansi lumens. However, if room light is available, the picture should be a maximum of 266 cm wide. The projector was launched in 2005 and is no longer sold by the manufacturer. 1 x 0,55" DDP2000 DLP Chip

Display Type

2100

SVGA 4/3 Ti Digital Light Processing Chip ω700 Lux (bei 200 cm Screen)

Ansi-Lumen Contrast **Black Level** Offset

2000:1 full on/off 1,0500 min. Lumen 2000:1 full on/off 0,351 min. Lumen

SVGA 800 x 600 480.000 Pixel

200W VIP Lamp

Resolution

XGA 1024 x 768 compressed

Video Modes

PAL, SECAM, NTSC, HDTV 720p, 1080i, EDTV 480p, 576p

Standard-Portabel | External training and company presentations, as well as product

Application

presentations. Medium screen width or rooms with little light, max. 100 lumens.

Light Source Light Life

Operating Costs

Focus

Manual

Zoom

Manual 1,6

Objective

Throw Ratio

1,7-2,00:1

Audio

Yes

DVI-I Cinch Video in

Connections

S-Video in Mini Jack USB Typ B **RS232C**

Ceiling Mounting

Power

Size WxHxD 280 x 97 x 205 mm (11"x3,8"x8,1") 5,57 L/dm3


Operating Noise 34dB


2,00 kg / 4,41 lbs. Weight Vert.: +/-15° 90%

Frequenz H-sync: 15-70 kHz

65 fL / max. 399 cm screen width Foot-Lamberts

223 cd/m²





Keystone Illumination

Features

■ Kensington Slot■ Carl Zeiss lens

■ De-interlacer with 2: 3:2 pull down

2005 Discontinued (EOL) // Last update of the data: 2023-08-04

Status Data

More Details





Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.