

Vivitek DX883ST

VIVITEK DX883ST



A brief introduction to the Vivitek DX883ST. The short-throw DLP projector has an XGA 1024 x 768 resolution and a contrast of 15000:1. Thanks to the short-throw projection ratio of just 0.626:1, the projector does not stutter in the room. For a 2m wide image, the projector only needs to be 125 cm away from the screen. As the DX883ST is equipped with a microphone jack and 10W speakers, no additional audio system is required for presentations or training sessions. The HDMI MHL (Mobile High-Definition Link) port allows 1080p / 60 Hz image mirroring (screen mirroring) to be transmitted from the smartphone while it is being charged at the same time via the connection. It is also Full HD 1080P and 3D compatible. On the market since 2015, the model is no longer offered by the manufacturer Vivitek.



1 x 0,55" DLP Chip
XGA 4/3 Ti Digital Light Processing Chip

Projector	3300	Screen	1100 Lux (bei 200 cm Screen)
Contrast	15000:1 full on/off		15000:1 full on/off
Black Level Offset	0,2200 min. Lumen		0,073 min. Lumen

Resolution: XGA 1024 x 768
786.432 Pixel
WUXGA 1920 x 1200 compressed
Video Modes: Pal, SECAM, NTSC, HDTV 720p, 1080i, 1080p, 3D, EDTV 480p, 576p
Disc Recognition: DVD | HD Blu-ray (komprimiert) | 3D Blu-ray (komprimiert) | 4K UHD Blu-ray
3D Compatibility: Frame-Packing (Full HD 3D) | Side-by-Side | Frame Sequential (3D Ready)
Application: Short Distance | Medium screen width or rooms with a little more ambient light, max. 200 lumens.
Light Source: 240 / 190W im Eco Mode Lamp
Light Life: Articiel Nr.: 5811119560-SVV
3500 h. 7000 in Eco Mode
Operating Costs: -
Focus: Manual
Zoom: No Zoom
Objective: F=2,8 f=7,51mm
Throw Ratio: 0,626:1
Audio: 2 x 10W
Connections: 2 x HDMI 1.4 mit MHL in
DVI in
D-sub 15pin in und out
Cinch Video in
Cinch Stereo in



Brief Introduction
Beta 2.5

Display Type

Ansi-Lumen
Contrast
Black Level
Offset

Resolution

Video Modes
Disc Recognition
3D Compatibility

Application

Light Source

Light Life

Operating Costs

Focus

Zoom

Objective

Throw Ratio

Audio

Connections

S-Video in
Mini Jack Audio in und out
USB Typ A in
RS232C Din 9 pin in
RJ45 in
Mikrofon in
12V Trigge rout



Ceiling Mounting
Power
Size WxHxD
Operating Noise

Yes
3100 / 250W in Eco Mode
314 x 126 x 241 mm (12,4"x5"x9,5") 9,53 L/dm³
36 / 32 dB in Eco Mode

Weight
Keystone
Illumination

3,24 kg / 7,14 lbs.
Vert.: +/-40°
85%

Frequenz

-

Foot-Lamberts

102 fL / max. 500 cm screen width
349 cd/m²

Features

- Real Full HD 3D
- Full HD 1080P compatible
- Eco Mode
- Kensington Slot
- BrilliantColor™
- Lan network compatible.
- Short-throw projector
- 6-segment colour wheel

Status
Data

2015 Discontinued (EOL) // Last update of the data: 2023-09-20



More Details



HCinema

<https://www.projector-database.com/pro/vivitekdx883st-en.html>

Due to our ongoing commitment to continuously improve the quality of our projector database, this brochure is also subject to change without notice. HCinema is not responsible for any errors or omissions contained in product descriptions.